

Sandstone Stimulation Tube

Industrial Oilfield Chemical Grade

1. PRODUCT OVERVIEW

A high-purity dry powder optimized to maintain pore-throat space due to sandstone-type buildup.

- **Product Code:** SS-1076
- **CAS Number:** Proprietary
- **Synonyms:** Mud-acid dissolver, Sandstone stimulant

2. TYPICAL PHYSICAL & CHEMICAL PROPERTIES

Property	Specification / Value	Test Method
Appearance / Physical State	Yellow Tube	Visual
Purity / Assay	≥ 99.5% Active	Lab Test
Density	1.63 g/mL at 25 °C	Calculated
Bulk Density	0.75 g/ml at 25 °C	Calculated
Melting / Freezing Point	Room temperature Powder Literature	
Moisture / Water Content	≤ 0.1%	Oven
Solubility	Miscible in water	Visual

3. APPLICATIONS & USES

- **Industrial:** Place 1-tube in a well head, and allow tube to mix with fresh-water to dissolve tube contents. Contents dissolve pore-throat volume material such as sandstone and other silica-based material.
- This is a self-contained tube-like cartridge that is dropped directly into a well to release components to target silicates and sand.

- The dry tube is placed in a wellbore, and is ejected into the wellbore. The tube reacts with water when travelling to the well-perforations.
 - To further enhance product effectiveness, place a drum of low-calcium water ahead of the tube to be placed in the wellbore.
-

4. STORAGE & HANDLING

- **Handling:** Provide adequate ventilation. Wear appropriate personal protective equipment (PPE) including chemical safety goggles and gloves. Avoid breathing vapors.
 - **Storage Conditions:** Store in a cool, dry, well-ventilated area away from incompatible materials (e.g., strong oxidizers). Keep container tightly sealed when not in use.
 - **Shelf Life:** 24 Months from the date of manufacture when stored under recommended conditions.
-

5. PACKAGING AVAILABILITY

Container Type	Volume / Weight	Part Number
----------------	-----------------	-------------

Tube	~400 mL	SS-1076-T
------	---------	-----------

6. SAFETY & REGULATORY

- **Safety Data Sheet (SDS):** A comprehensive SDS is available upon request. Always read and understand the SDS before handling this product.
- **Hazards:** Refer to GHS labels on the packaging.